

US009543415B2

(12) United States Patent Wang et al.

(54) THIN FILM TRANSISTOR DRIVING BACKPLANE AND MANUFACTURING METHOD THEREOF, AND DISPLAY PANEL

(71) Applicant: **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(72) Inventors: **Zuqiang Wang**, Beijing (CN); **Chien Hung Liu**, Beijing (CN)

(73) Assignee: **BOE TECHNOLOGY GROUP CO.,** LTD., Beijing (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 293 days.

(21) Appl. No.: 14/362,971

(22) PCT Filed: Dec. 12, 2013

(86) PCT No.: **PCT/CN2013/089180**

§ 371 (c)(1),

(2) Date: **Jun. 5, 2014**

(87) PCT Pub. No.: WO2015/043084PCT Pub. Date: Apr. 2, 2015

(65) **Prior Publication Data**US 2016/0218124 A1 Jul. 28, 2016

(30) Foreign Application Priority Data

Sep. 27, 2013 (CN) 2013 1 0451705

(51) Int. Cl. H01L 21/00 (2006.01) H01L 31/062 (2012.01) (Continued)

(52) **U.S. Cl.**CPC *H01L 29/66757* (2013.01); *H01L 27/124*(2013.01); *H01L 27/1259* (2013.01);
(Continued)

(10) Patent No.: US 9,543,415 B2

(45) **Date of Patent: Jan. 10, 2017**

(56) References Cited

U.S. PATENT DOCUMENTS

7,015,122 B2* 3/2006 Lee	
	257/E21.413
7,235,850 B2 * 6/2007 Koo H	
	257/291

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1011319585 A	2/2008
CN	101335188 A	12/2008
	(Continued)	

OTHER PUBLICATIONS

First Office Action issued by State Intellectual Property Office of the People's Republic of China dated Jul. 9, 2014, 4pgs.

(Continued)

Primary Examiner — Calvin Lee (74) Attorney, Agent, or Firm — Ladas & Parry LLP

(57) ABSTRACT

The embodiments of the present invention provide a thin film transistor driving backplane and a manufacturing method thereof, and a display panel. The manufacturing method may comprise: manufacturing a backplane base disposed with a plurality of active device structures; disposing an electrode layer on the backplane base; and manufacturing the electrode layer into a source electrode, a drain electrode and a pixel electrode integrally disposed with the drain electrode by one patterning process. According to the embodiment of the present invention, the electrode layer is manufactured into a plurality of source electrodes, drain electrodes and pixel electrodes, integrally disposed with the drain electrode, by one time patterning process, so that the source electrode, the drain electrode and the pixel electrode are all at the same electrode layer, and the source electrode, (Continued)



